

**PS22**

-

**0**

-

**18**

-

**165**

**K**

**180**

**K**

### SERIES

**PS22:** NO (NORMALLY OPEN)  
(Opens on pressure rise)

**PS23:** NC (NORMALLY CLOSED)  
(Opens on pressure fall)

### TERMINATION

(Signifies lead length in inches)

**00:** 1/4" Male Spade Terminals

**06 to 72:** 6" to 72" Wire Leads

### OPEN (CUT-OUT)

0 to 700 PSI  
(0 to 48.3 Bar)

### CLOSE (CUT-IN)

0 to 700 PSI  
(0 to 48.3 Bar)

### FITTINGS

- 0:** 1/4" Female Flare Fitting w/Deflator
- 1:** 1/8 Male Pipe Thread
- 2:** 1/4" Male Pipe Thread
- 3:** 3/8" Male o-ring
- 4:** 1/4" Solder

### TOLERANCE

- |                  |                  |
|------------------|------------------|
| <b>C:</b> +/- 3  | <b>L:</b> +/- 11 |
| <b>D:</b> +/- 4  | <b>M:</b> +/- 12 |
| <b>E:</b> +/- 5  | <b>N:</b> +/- 13 |
| <b>F:</b> +/- 6  | <b>P:</b> +/- 14 |
| <b>G:</b> +/- 7  | <b>R:</b> +/- 15 |
| <b>H:</b> +/- 8  | <b>Y:</b> +/- 20 |
| <b>J:</b> +/- 9  | <b>Z:</b> +/- 30 |
| <b>K:</b> +/- 10 |                  |